



TYRES FOR TRUCKS AND MINING TRUCKS

Tyres are manufactured under our own brand. It has sidewall markings «UkrTechProm», «SuperTechProm» and the logo of the «Ukrtechprom» corporation

**OWN TYRE BRAND
PRODUCTION**



ВЛН-5
175/80-16



УТР21
12.00R18



УТР-173
7.50-20



УТР-50
16/70-20



ИД-П 284
1200x500-508



О-47АМ
1100x400-533



ИП-184
1220x400-533



МР-913
15.00-21



ВИ-3
1300x530-533



СТР-66
525/70R21



ИД-370
1350x550-533R



ВФ-76Б
18.00-25



ВФ-166А
21.00-33

Rim diameter, inches	Tyre size	Tyre model	Loading limit, kg	Pressure corresponding the max loading, kPa	Load index	Tube	Recommended rim	Flap	Overall diameter, mm	Section width, not more than, mm	Static radius, mm	Speed limit, km/h (Speed Index)
Tyres for trucks												
16	175/80-16 (6.95-16)	ВЛН-5	515	210	85	6.95-16	5j	-	692	178	326	150(P)
18	12.00R18 (320R457)	УТР21	2180	490	135	12.00-18	465-228 (228Г-457)	205-457	1084	337	505	110(K)
20	7.50-20 (220-508)	УТР-173	1360 single 1250 dual	440	119 116	7.50-20 УК-2	6.0-20	6.7-20	928	213	443	100(J)
20	16/70-20	УТР-50	3075	500	154	16/70-20	13.0-20	300-508	1090	410	498	80(F)
20	1200x500-508 (500/70-20)	ИД-П 284	4000	520	156	1200x500-508	400Г-508	475-508	1185	475	548	80(F)
21	1100x400-533 (400/70-21)	О-47АМ	2900	360	145	1100x400-533	330-533	340-533	1120	410	525	90(G)
21	1220x400-533 (400/85-21)	ИП-184	2650	340	142	1220x400-533	310-533	340-533	1200	418	560	90(G)
21	15.00-21 (425/90-21)	МР-913	4625	600	161	1220x400-533	330-533 440-533	475-533	1308	430	610	100(J)
21	1300x530-533 (530/70-21)	ВИ-3	4000	390	156	1300x530-533	440-533	475-533	1280	525	585	80(F)
21	525/70R21	СТР-66	4500	500	160	1300x530-533	440-533	475-533	1285	525	592	100(J)
			4750	570	162							90(G)
			5000	600	164							80(F)
21	525/70R21	СТР-66	6300	650	172	1300x530-533	440-533	475-533	1285	525	592	65(D)
21	1350x550-533R (550/75R21)	ИД-370	4500	540	160	1300x530-533	440-533	475-533	1350	550	625	90(G)
			4750	560	162							80(F)
			5000	590	164							70(E)
21	1350x550-533R (550/75R21)	ИД-370	6300	785	172	1300x530-533	440-533	475-533	1350	550	625	65(D)
Tyres for mining trucks												
25	18.00-25	ВФ-76Б	8750	575	183	18.00-25	13.00	18.00-25	1615	498	745	50(B)
33	21.00-33	ВФ-166А	12150	575	195	21.00-33	15.00	21.00-33	1940	571	905	50(B)



TYRES FOR AGRICULTURAL MACHINERY

Tyres are manufactured under our own brand. It has sidewall markings «UkrTechProm», «SuperTechProm» and the logo of the «Ukrtechprom» corporation

**OWN TYRE BRAND
PRODUCTION**



DT-48
5.00-10



ST-421
6L-12



UTP-77
500/50R17



KΦ-97
16.5/70-18



UTP-223
9.00-20



UTP-14
21.3R24



ДΦ-16A
28.1-25



Φ-37
23.1R26



Φ-268 Φ-289
9.5R32 9.5R42



DN-101
30.5LR32



Д-2A
15.5R38



DE-16 DE-17
9.5R44 9.5R48

Rim diameter, inches	Tyre size	Tyre model	Loading limit, kg	Pressure corresponding the max loading, kPa	Load index	Tube	Recommended rim	Overall diameter, mm	Section width, not more than, mm	Static radius, mm	Speed limit, km/h (Speed Index)
10	5.00-10	DT-48	335	300	70	4.50-10	4.00E	505	145	235	30(A6)
12	6L-12	ST-421	160	100	44	6-12	5JA	570	155	267	30(A6)
17	500/50R17	UTP-77	3250	350	149	tubeless	16.00x17	932	503	420	40(A8)
18	16.5/70-18	KΦ-97	3650	410	153	16.5-18	330-462	1065	425	484	30(A6)
18	16.5/70-18	KΦ-97	3650	410	153	tubeless	330-462	1065	425	484	30(A6)
20	9.00-20 (240-508)	UTP-223	1120	260	112	7.50-20	W8, W7	930	234	430	30(A6)
24	21.3R24 (530R610)	UTP-14	2500 3350	160 240	140 150	21.3-24	DW18	1400	540	640	30(A6) 50(B)
25	28.1-25 (720-635)	ДΦ-16A	9250	360	185	23.1-26 28.1-25	24.00-25/2.5	1730	710	768	50(B)
26	23.1R26	Φ-37	3150 3650	120 160	148 153	23.1-26	DW20	1605	587	715	40(A8)
32	9.5R32	Φ-268	1120	160	112	9.5-32	W8	1245	241	579	40(A8)
32	30.5LR32	DN-101	5450	160	167	30.5-32	DW27	1820	775	810	40(A8)
38	15.5R38	Д-2A	2120	160	134	13.6-38	W14L	1570	394	720	40(A8)
42	9.5R42	Φ-289	1320	240	118	9.5-42	DW8	1500	241	720	30(A6)
44	9.5R44	DE-16	1750	330	127	tubeless	W8	1550	241	735	40(A8)
48	9.5R48	DE-17	1850	320	129	tubeless	W8	1650	241	785	40(A8)

0 800 605 612

SuperTechProm
corporation

utp.ua